



RATOTM

www.rato-europe.com

3

EDITION
2017

MOTOPOMPE AD ALTA PRESSIONE 50m E 90m HIGH PRESSURE MOTORPUMPS

APPLICAZIONI - APPLICATIONS



RT50YB50

RT50YB100



Caratteristiche:

RT50YB50-3.8Q e RT50YB100-7.2Q
per irrigatori ed antincendio

Features:

RT50YB50-3.8Q e RT50YB100-7.2Q
for sprinklers and fire fighting



Modello - Model		RT50YB50-3,8Q		RT50YB100-7,2Q	
Motore	Engine	R210		R390	
Tipo	Type	4 tempi, raffreddamento ad aria / 4-stroke, Air-cooled			
Carburante	Fuel	Benzina / Gasoline		Benzina / Gasoline	
Cilindrata	Displacement	ml	212		389
Pompa	Pump Set				
Aspirazione	Suction port	Ø	50 (2")		50 (2")
Mandata	Discharge port	Ø	50 (2")		50 (2")
Capacità aspirazione	Suction head lift	m	7		7
Prevalenza massima	Total head lift	m	50		90
Portata massima	Discharge capacity	l / min	500		500
Dimensioni	Dimensions	LxWxH mm	500x395x446		610x480x537
Peso	Weight	Kg	29,5		64



www.rato-europe.com
E-mail: info@rato-europe.com



*A seguito dei costanti sforzi dedicati al miglioramento dei nostri prodotti, procedure e dati tecnici possono cambiare senza preavviso.
Due to constants efforts to improve our products, certain procedures and specifications are subject to change without notice.*